


Cush-A-Strip™

Submittal Sheets


- Manufactured from a thermoplastic elastomer, Cush-A-Strip is designed for use from -50°F to 275°F.
- Easy Stocking Packaged in 20 foot rolls in an E-Z dispenser box for convenience in handling and storage. Cush-A-Strip roll part number is S-716
- Easy Measuring Marked in ¼" increments for fast measuring and cutting, while eliminating waste.
- Lock-lip edges ensure that Cush-A-Strip will remain in place with a balanced grip.
- Clamps ordered separately. They are available with a standard bolt and nylon lock nut in steel (electro-dichromate), and stainless steel, in sizes ranging from ½" tube to 6" pipe.





(1) Cut appropriate length strip using the cutting schedule shown on right.



(2) Place the pipe on the Cush-A-Strip









Cush-A-Strip [™] Cutting Guide						
Clamp Part No.		Dimensions (Inches)				
Gold Plated Steel	Stainless Steel Type 304	Clamp Size O.D.	Tube Size O.D.	Pipe Size (Nom.)	Cutting Schedule	
N008C	NS008	1/2"	1/4"	-	7/8"	
N010C	NS010	5/8"	3/8"	-	1-1/8"	
N012C	NS012	3/4"	1/2"	1/4"	1-1/2"	
N014C	NS014	7/8"	5/8"	3/8"	2"	
N016C	NS016	1"	3/4"	-	2-1/4"	
N018C	NS018	1-1/8"	7/8"	1/2"	3"	
N020C	NS020	1-1/4"	1"	3/4"	3-1/4"	
N022C	NS022	1-3/8"	1-1/8"	-	3-5/8"	
N024C	NS024	1-1/2"	1-3/16"	-	3-7/8"	
N024C	NS024	1-1/2"	1-1/4"	1"	4"	
N026C	NS026	1-5/8"	1-3/8"	-	4-1/2"	
N028C	NS028	1-3/4"	1-1/2"	-	4-7/8"	
N030C	CS030	1-7/8"	1-5/8"	1-1/4"	5-1/4"	
N032C	CS032	2"	1-3/4"		5- ¹ /2"	
N034C	CS034	2-1/8"	1-7/8"	1-1/2"	6"	
N036C	CS036	2-1/4"	2"	-	6-3/8"	
N038C	CS038	2-3/8"	2-1/8"	-	6-3/4"	
N040C	CS040	2-1/2"	2-1/4"	-	7-1/4"	
N042C	CS042	2-5/8"	2-3/8"	2"	7-1/2"	
N044C	CS044	2-3/4"	2-1/2"	-	8"	
N048C	CS048	3"	2-3/4"	-	8-3/4"	
N050C	CS050	3-1/8"	2-7/8"	2-1/2"	9-1/4"	
N054C	CS054	3-1/4"	3"	-	9-1/2"	
N060C	CS060	3-3/4"	3-1/2"	3"	11"	
N068C	CS068	4-1/4"	4"	3-1/2"	12-1/4"	
N076C	CS076	4-3/4"	4-1/2"	4"	14"	
N092C	CS092	5- ³ /4"	-	5"	15- ¹ /2"	
N110C	CS110	6-7/8"	_	6"	18-1/2"	

^{*} Gold Plated Steel Clamps Supplied with Fixed Stud and Nylon Lock Nut

	Project Information:	Approval Stamp:
Project:		
Date:	Phone:	
Architect / Engineer:		
Contractor:		
Address:		
Notes 1:		

^{*} Stainless Steel Clamps Supplied with fixed Stud and Nylon Lock Nut from 1/2" through 1-3/4" Sizes and 1-7/8" through 6-7/8" Sizes are supplied with a Loose Bolt and Hex Nut