WESANCO ZSI STRUT SERPENT®



Warning: Reading This Flyer Will Change The Way You Think About Strut Clamps Forever...









Supports Pipe and Tube.

- Electrical and Mechanical Applications.
- Very Clean Appearance After the Assembly is Complete.
- Easy Relocation of Conduit, Pipe, or Tube Prior to Final Alignment.
- Secure the Conduit, Pipe, or Tube Above and/or Below the Strut.
- Perfect for Trapeze Applications.
- A significant reduction of 60% in labor costs to install.
- Worm Gear fastening method that ensures the proper torque-tension.



Patented






The Simplicity of the Strut Serpent!

Worm Gear Strut Clamp





Part Number	Size	Outside Diameter	Conduit	Stainless Steel Material
SSEMT050	½" (13mm)	0.706 (18mm)	Electrical Metallic Tubing (EMT)	Type 301
SSEMT075	³ / ₄ " (19mm)	0.922 <i>(23mm)</i>		
SSEMT100	1" <i>(25mm)</i>	1.163 <i>(30mm)</i>		
SSEMT125	1- ¹ / ₄ " (32mm)	1.510 <i>(38mm)</i>		
SSEMT150	1-½" (38mm)	1.740 <i>(44mm)</i>		
SSEMT200	2" <i>(51mm)</i>	2.197 (56mm)		
SSGRC050	½" (13mm)	0.840 <i>(21mm)</i>	Galvanized Rigid Steel Conduit (GRC)	Type 301
SSGRC075	³ / ₄ " (19mm)	1.050 <i>(27mm)</i>		
SSGRC100	1" <i>(</i> 25mm)	1.315 <i>(33mm)</i>		
SSGRC125	1- ¹ / ₄ " (32mm)	1.660 <i>(42mm)</i>		
SSGRC150	1-½" (38mm)	1.900 <i>(48mm)</i>		
SSGRC200	2" (51mm)	2.375 (60mm)		



Strut Serpent® - New Installations

Step 1: Place Strut Serpent over pipe and into channel



Step 2: Hook Teeth onto channel In-turned edges and Tighten with a wrench Secure



Step 3: Completed. Simple!

